

SAFETY DATA SHEET

1. Product and company (manufacturer) identification

Product: Eslotight B
Manufacturer: Sekisui Chemical Co., Ltd.
Address: Toranomon 2-10-4, Minato-ku, Tokyo 105-8566
Responsible section: Urban Infrastructure & Environmental Products Company
 Pipe Systems Division
Telephone: +81-3-6748-6492
Urgent telephone: +81-3-6748-6492
Fax: +81-3-6748-6564
Urgent contact: Same as above
Application & restriction: Bonding agent for polyvinyl chloride piping system for sewers.
 Other applications are prohibited.
Document number: Es-B

2. Hazards identification

GHS Classification

| | | | |
|--|--|--------------------------------------|-----------------------------|
| Physicochemical hazards: | Explosives | Not classified | |
| | Flammable gases | Not classified | |
| | Aerosols | Not classified | |
| | Oxidizing gases | Not classified | |
| | Gases under pressure | Not classified | |
| | Flammable liquids | Not classified | |
| | Flammable solids | Not classified | |
| | Self-active chemicals | Not classified | |
| | Pyrophoric liquids | Not classified | |
| | Pyrophoric solids | Not classified | |
| | Self-heating chemicals | Classification not possible | |
| | Chemicals which, in contact with water, emit flammable gases | Not classified | |
| | Oxidizing liquids | Not classified | |
| | Oxidizing solids | Not classified | |
| | Organic peroxides | Not classified | |
| | Substances corrosive to metals | Classification not possible | |
| | Desensitized explosives | Not classified | |
| | Health hazards: | Acute toxicity (oral) | Not classified |
| | | Acute toxicity (dermal) | Not classified |
| | | Acute toxicity (inhalation: gas) | Not classified |
| | | Acute toxicity (inhalation: vapor) | Classification not possible |
| | | Acute toxicity (inhalation: dust and | Classification not possible |
| | | Skin corrosion/irritation | Category 1 |
| Eye damage/irritation | | Category 1 | |
| Respiratory sensitization | | Not classified | |
| Skin sensitization | | Not classified | |
| Germ cell mutagenicity | | Not classified | |
| Carcinogenicity | | Not classified | |
| Reproductive toxicity | | Not classified | |
| Specific target organ toxicity (single exposure) | | Not classified | |
| Specific target organ toxicity (repeated exposure) | Not classified | | |
| Environmental hazards: | Aspiration hazard | Not classified | |
| | Hazard to the aquatic environment (Acute hazard) | Not classified | |
| | Hazard to the aquatic environment (Long-term hazard) | Not classified | |
| | Hazard to the ozone layer | Not classified | |

Pictogram or symbol:



Signal word:

Danger

Hazard statement: (H314) Causes severe skin burns and eye damage
Precautionary statement: Do not breathe dust/fume. (P260)
Wash hands thoroughly after handling. (P264)
Wear protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331)
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (P303+P361+P353)
Wash contaminated clothing before reuse. (P363)
IF INHALED: Remove victim to fresh air and keep comfortable for breathing. (P304+P340)
Immediately call a POISON CENTER or doctor/physician. (P310)
Specific treatment (see the label). (P321)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Store locked up. (P405)
Dispose of contents/container in accordance with local/regional/national/international regulations. (P501)

3. Composition/information on ingredients

Nature of composition: Mixture
Chemical or common name: Modified Polythiol
Hazardous ingredients: Tris(dimethylaminomethyl)phenol, Carbon black

| Component | Content | CAS Number | Reference Number in Gazetted List in Japan | Others |
|---------------------------------|---------------|------------|--|--------|
| Polythiol | 55 to 64 % | Registered | Registered | |
| Tris(dimethylaminomethyl)phenol | 1 to 10 % | 90-72-2 | (3)-714 (3)-762 (3)-776 | |
| Calcium carbonate | 25 to 34 % | 471-34-1 | (1)-122 | |
| Carbon black | Less than 1 % | Registered | Registered | |

※The content is listed as a range as it is confidential information.

4. First-aid measures

If vapor is inhaled: Take the affected person to a clean-air space and give him rest in a easy-breathing pose.
Seek physician's counsel as may be needed.

If attached to skin: Immediately wipe off and wash the skin with plenty water and soap.
Take off the contaminated clothing's for cleaning.
Seek physicians counsel if he suffers from irritation or drowsiness.

If gets in eye: Rinse cautiously with plenty water over 15 minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
Seek physician's counsel.

If swallowed: Immediately seek physician's counsel.
Rinse the mouth well and drink a lot of water to vomit.

Special note to physician: No information

5. Fire-fighting measures

Extinguishing agents: Carbon dioxide, powder agent, foam agent
Prohibited extinguishing agent: Water flux
Specific hazards: Fire may cause to generate irritant, toxic or erosive gas.
Easily flammable. It will readily be ignited by heat, spark or flame.
Heating of container may cause explosion.
Easily inflammable liquid and vapor.

Proper extinguishing method: Remove surrounding combustibles and use extinguishing agents.
Use foam agent to choke a large scale fire.
Fight against fire standing to its windward as much as possible and wear Respirator if necessary.
The use of water can spread the fire and be dangerous.

6. Accidental release measures

Health hazard precaution, protective wear and first-aid Workers should use protective wears (See Chapter 8) to prevent contact with the spilt adhesive and inhalation of its vapor.
Rope off the crowd from the leak spot.

Environmental hazard precaution: Prevent flow out to rivers, etc. so as not to badly affect the environment.

Recovery and neutralization: For small scale leakage, use absorbent (sawdust, dirt, sand, waste rug) to remove most of the spill and collect in sealed containers.
For large scale leakage, build bank around the spill and lead the liquid to a safer place for recovery.
Alternatively, absorb the spillage onto sand, rags, etc. and collect it in a sealed container.

Prevention of secondary casualty: Quickly remove all the combustibles from around the leak spot and provide extinguishers ready for use.

7. Handling and storage precautions**Handling**

| | |
|---------------------------------------|---|
| Technical measures: | Use protective wears if inhalation or skin contact is foreseen. No open flames. |
| Local & total ventilation: | Handling work must be practiced in a room where local or total ventilation facility is functioning. |
| Safe handling: | Ban of high temperature substance, sparking and fire at nearby points. Prohibition of eating, drinking and smoking while the product is used. Wash hands well after handling. Avoid contact of the product with eye, skin and clothing. Do not inhale vapor, mist and spray of the product. Handle it only after reading and understanding all the precautions. Use the product only in a well ventilated room or outdoors. |

Storage

| | |
|----------------------------|--|
| Storing conditions: | Store in a remote room from heat, sparks and naked flame. No smoking in the storage room. Store in a cool, ventilated room. Lock the storage room. |
|----------------------------|--|

8. Exposure controls and personal protection**Facility measures:**

Local ventilation of closed work room or total proper ventilation to prevent vapor inhalation.

Control concentration:

Not determined

Permissible concentration (Exposure limit, Biological exposure guide line)

Japan society for occupational health.
(2005 version)

Not determined

ACGIH (2005 version) TLV-TWA

Not determined

Protective wears:

| | |
|----------------------------------|--|
| Respiratory protection: | Use aspirator with appropriate filter |
| Hand protection: | Impermeable gloves |
| Eye protection: | Glasses-type goggles with side plates. |
| Skin and body protection: | Long-sleeve fatigue uniform |

Hygienic measures:

Wash hands well after handling.

9. Physical and chemical properties

| | |
|---|--|
| Physical state | Viscous Liquid |
| Color | Gray |
| Odor | Characteristic |
| Melting point/Freezing point | No data available |
| Boiling point or initial boiling point | No data available |
| Flammability | No data available |
| Lower and upper explosion limit/flammability limit | No data available |
| Flash point | 220°C |
| Auto-ignition temperature | No data available |
| Decomposition temperature | No data available |
| pH | Not applicable |
| Dynamic viscosity | Not applicable |
| Solubility | Insoluble in water, soluble in common organic solvents |
| n-octanol/water partition coefficient: | No data available |
| Vapor pressure | Not applicable |
| Density and/or relative density | ca. 1.26 |
| Relative vapor density | Heavier than air |
| Particle characteristics | No data available |

10. Stability and reactivity**Stability:**

Stable under normal conditions and handling.

Chemical stability:

Stable under normal conditions and handling.

Possibility of hazardous reaction:

reacts with epoxy, isocyanate, strong acid.

Prohibitive conditions:

Heat

Prohibitive contact:

Oxidizing agent, epoxy, etc.

Hazardous decomposed substances:

Generates amine and organic matter by thermal decomposition.

| | |
|--|--|
| 11. Hazard information | |
| Acute toxicity (oral) | Measurements of compound ATE mix=2448mg/kg The product, as the mixture, falls in Not classified. |
| Acute toxicity (dermal) | Measurements of compound ATE mix=2299mg/kg The product, as the mixture, falls in Not classified. |
| Skin corrosion/irritation | The product, as the mixture, falls in Category 1 (Causes skin irritation). |
| Eye damage/irritation | The product, as the mixture, falls in Category 1 (Causes eye irritation). |
| Skin sensitization | The product, as the mixture, falls in Not classified. |
| As a result of the Ministry of Health, Labor and Welfare's toxicity study, mutagenicity tests using micro-organisms and chromosomal aberration tests using mammalian cultured cells showed mutagenicity exceeding the prescribed criteria and may cause health problems. | |
| 12. Ecological information | |
| Ecotoxicity: | None known at present. |
| Persistence/degradability: | None known at present. |
| Ecological accumulative property: | None known at present. |
| Mobility in soil: | None known at present. |
| Hazard to the aquatic environment (Acute hazard): | No data available. |
| Hazard to the aquatic environment (Long-term hazard): | No data available. |
| Hazard to the ozone layer: | Does not contain any ingredients listed in the Annexes to the Montreal Protocol. Classification not possible. |
| 13. Notes on disposal | |
| Residual & waste: | In the disposal of residual and other wastes, observe the relevant laws /regulations and local government rules. Users of the product should contract with the local government or licensed 'Industrial Waste Processors' for disposal of waste. It is important to let the contractor know well of fire and health hazards of the product, prior to disposal. |
| Contaminated containers & packages: | Clean the containers for reuse or dispose them properly in accordance with relevant regulations and local government rules. Completely empty containers prior to disposal. |
| 14. Transport information | |
| International rule | |
| UN number: | 3259 |
| Proper shipping name: | AMINES, SOLID, CORROSIVE, N.O.S. or POLYAMINES, SOLID, CORROSIVE, N.O.S. |
| UN classification: | Class 8 |
| Packing Grade | III |
| Sea Pollution Prevention Act | Not applicable |
| Domestic control: | |
| Guidance Number | 154 |
| Onshore control info. | Observe the Fire Defense Law. |
| Offshore control info. | Observe the Marine Vessel Safety Law. |
| Air cargo control info. | Observe the Aviation Law. |
| Special safety measure: | Observe the Fire Defense Law. On-board containers of hazardous material must be piled firmly and orderly to avoid falling, tumbling and breaking. Cargo of hazardous material must be transported in a way the containers or the material itself do not suffer severe friction and vibration. If possible cause of casualty, such as heavy leakage, is found during transportation, try to remedy the situation and notify the fact to the nearby fire department or the relevant bureau. The driver carrying hazardous material must hold Yellow Card. Do not load hazardous materials together with food and feedstuff. |
| 15. Regulatory information | |
| Labor Safety and Hygiene Law: | Hazardous materials to be notified to the authority (Chapter 57, Section 2) (Carbon black) Hazardous materials to be posted (Chapter 18 of Ordinance) (Not applicable) Mutagenicity chemical substance (Not applicable) Carcinogenicity of chemical substances (Ordinance on Industrial Safety and Health Chapter 34,Section 2-4) (Not applicable) Chemical substances that cause skin and other skin disorders (related to Article 22 of the Law). (Tris(dimethylaminomethyl)phenol) |
| Fire Defense Law: | Not applicable |
| PRTR Law: | Not applicable |
| Poisonous & Deleterious Substance Control Law: | Not applicable |
| Sea Pollution Prevention Act | Not applicable |

16. Other information**Literature:**

- 1) Chemicals Safety Data Sheet (MSDS) Part 1: Content and Order of Items
- 2) Guideline for MSDS Edition (Revised Edition) by Japan Chem. Ind. Assoc.
- 3) GHS Classification Database, Site of National Institute of Technology and Evaluation
- 4) Hazard Handbook of Chemicals by Japan Industrial Safety and Health Association
- 5) Hazard communication of chemicals based on GHS–Labelling and Safety Data Sheet (SDS) JIS Z 7253:2012

This data sheet is edited by referring to currently available information, however, it is not intended to guarantee the data values or the precision of contained information. The precautions mentioned above are for ordinary handling and use only therefore please handle with care by implementing appropriate safety measures for new application and usage.